

Heat Shrink Products



Product Data Sheet

RYLMWG12	Double Glue Lined Medium 12.0mm-4.0mm 1.2m/length
RYLMWG22	Double Glue Lined Medium 22.0mm-7.0mm 1.2m/length
RYLMWG34	Double Glue Lined Medium 34.0mm-10.0mm 1.2m/length
RYLMWG40	Double Glue Lined Medium 40.0mm-12.0mm 1.2m/length
RYLMWG56	Double Glue Lined Medium 56.0mm-18.0mm 1.2m/length
RYLMWG92	Double Glue Lined Medium 92.0mm-27.0mm 1.2m/length
RYLMWG120	Double Glue Lined Medium 120.0mm-36.0mm 1.2m/length
RYLMWG140	Double Glue Lined Medium 140.0mm-47.0mm 1.2m/length



Primary

Product Brand

Rylec

Range of Product

Heat Shrink Glue Lined

Profile

Material EVA, Hot melt Adhesive

Sizes 12.0mm-4.0mm, 22.0mm-7.0mm, 34.0mm-10.0mm, 40.0mm-12.0mm
56.0mm-18.0mm, 92.0mm-27.0mm, 120.0mm-36.0mm, 140.0mm-47.0mm

Colours Black

Length 1.2m

Shrink temperature 125degC to 200degC, operating temperature 45degC to 125degC

Water proof, rated voltage 600v



36 Terrence Road
Brendale Q 4500

☎ +61 7 3881 6115

✉ sales@gtsonline.com.au

🌐 gtsonline.com.au

The information provided explains a general description, and make up of the product contained herein.

This is not to be used for determining suitability or reliability for any user applications, it is the responsibility of the user to determine their own risk analysis.

GTS shall not be responsible or liable for misuse of this information encompassing this product.